



## Full Synthetic Engine Oil

Eco Ultra® Full Synthetic Engine Oil is blended with the highest quality synthesized base stocks, high quality re-refined base stocks, and contains a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins.

Eco Ultra Full Synthetic Engine Oil also protects engines from sludge, rust and acid build-up. This oil performs efficiently in gasoline engines and is outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 0W-20</u>
Viscosity @ -35°C, cP	D-5293	6000
Viscosity @ -30°C, cP	D-5293	N/A
Viscosity @ 40°C, cSt	D-445	45.00
Viscosity @ 100°C, cSt	D-445	8.50
Viscosity Index	D-2270	160
Flash Point, COC, °C	D-92	213
Flash Point, COC, °F	D-92	415
Pour Point, °C	D-97	-40
Pour Point, °F	D-97	-40
Color	D-1500	2.0
Gravity, °API	D-287	32.0

Meets or exceeds the following tests and requirements:

API Service Classification - SN, ILSAC GF-5  
Chrysler MS-11999, MS-12007, MS-12015, MS-6395-S  
Resource Conserving  
Honda/Toyota Genuine Oils

EO-21/07.10.17