



Multi-Vehicle Synthetic Blend Automatic Transmission Fluid

Eco Ultra® Multi-Vehicle Synthetic Blend Automatic Transmission Fluid (ATF) is a multi-functional transmission fluid for numerous makes of passenger cars, trucks, construction and mining equipment, farm machinery and other mobile and industrial systems.

Eco Ultra Multi-Vehicle Synthetic Blend ATF is blended with highly re-refined Group II base oils and offers many performance benefits, including superior cold temperature performance characteristics, wide range of seal compatibility, excellent wear protection, superior frictional characteristics with excellent friction retention and smooth shifting. It also has excellent corrosion and rust preventive properties, as well as rigid anti-foam characteristics. It will not cause excessive seal swell or shrinkage, nor will seals excessively harden or soften.

This ATF allows for inventory optimization as it meets multiple applications and provides excellent service in a wide variety of automatic transmission applications.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>TEST SPECIFICATIONS</u>
Viscosity @ 40°C, cSt	D-445	30.99
Viscosity @ 100°C, cSt	D-445	7.14
Viscosity Index	D-2270	205
Flash Point, COC, °C (°F)	D-92	208 (406)
Pour Point, °C (°F)	D-97	-48 (-54)
Color	D-1500	Red
Gravity, °API	D-4052	32.9

Recommendations:

Service fill in Mercon, Chrysler (ATF +3 & ATF +4), Honda/Acura, Hyundai, Jeep, Mercedes-Benz, Mitsubishi (Diamond SP-II or SP-III), Nissan (Matic D, J, or K)/Infiniti, Saturn, Toyota (T-III & T-IV)/Lexus/Scion, VW/Audi, most European vehicles including BMW & Volvo, most Asian vehicles including Daewoo, Isuzu, Kia, Mazda, and Suzuki.

Not for use in transmissions requiring Ford Type F or Dexron®VI, Mercon® SP, LV or in Continuously Variable Transmission (CVT) applications. Always consult your owner's manual where specific automatic transmission fluids are recommended.

See Page 2 for list of suitable for use applications.

TO-12/07.10.17



List of Suitable for Use Applications for Eco Ultra® Multi-Vehicle Synthetic Blend ATF

Allison C4
Audi G052025A2
Audi G052025A1
BMW LA2634
BMW LT71141
Dexron
Dexron II
Dexron III D
Dexron III G
Dexron III H
Esso LT 71141
Ford Mercon
Ford Mercon V
Honda/Acura ATFZ1 (except
CVT's)
Hyundai SPII
Hyundai SPIII
Idemitsu K17
JWS 3309
Kia SPII
Kia SPIII
MAN 339 V1
MAN 339 Z1
MAN 339 Z2
Mazda ATF 111
Mazda ATF MV
Mercedes Benz 236.3
Mercedes Benz 236.5
Mercedes Benz 236.7
Mercedes Benz 236.9
Mercedes Benz 236.10
Mitsubishi Diamond SP
Mopar ATF +3
Mopar ATF +4
Nissan Matic D
Nissan Matic J
Nissan Matic K
Shell LA2634
Subaru ATFHP
Texaco 7045E
Texaco ETL8072 B
Texaco N402
Toyota Type TIII
Toyota Type TIV
Voith 55.6335.32 (G607)
Volvo 97340
ZF TEML 03D
ZF TEML 04D
ZF TEML 14A
ZF TEML 14B
ZF TEML 16L
ZF TEML 17C

TO-12/07.10.17