



Full Synthetic Engine Oils

Eco Ultra® Full Synthetic Engine Oil is blended with the highest quality synthesized base stocks, high quality re-refined base stocks, and contains a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins.

Eco Ultra Full Synthetic Engine Oil also protects engines from sludge, rust and acid build-up. This oil performs efficiently in gasoline engines and is outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 0W-20</u>	<u>SAE 5W-20</u>	<u>SAE 5W-30</u>	<u>SAE 10W-30</u>
Viscosity @ -35°C, cP	D5293	6000	N/A	N/A	N/A
Viscosity @ -30°C, cP	D5293	N/A	4600	5800	N/A
Viscosity @ -25°C, cP	D5293	N/A	N/A	N/A	5800
Viscosity @ 40°C, cSt	D445	45.00	44.00	58.00	63.00
Viscosity @ 100°C, cSt	D445	8.50	8.30	10.50	10.80
Viscosity Index	D2270	170	160	170	170
Flash Point, COC, °C	D92	213	213	213	213
Flash Point, COC, °F	D92	415	415	415	415
Pour Point, °C	D97	-40	-40	-40	-40
Pour Point, °F	D97	-40	-40	-40	-40
Color	D1500	2.0	2.0	2.0	2.0
Gravity, °API	D287	36.0	35.5	36.0	36.0

Meets or exceeds the following tests and requirements:

- API Service Classification - SP, ILSAC GF-6A
- Chrysler MS-11999, MS-12007, MS-12015, MS-6395-S Resource Conserving
- Ford Motor Company - WSS-M2C945A, WSS-M2C946A
- Honda/Toyota Genuine Oils

NOTE: Certain tests apply to specific SAE grades.