



Full Synthetic Engine Oils

Eco Ultra® Full Synthetic Engine Oils are blended with the highest quality synthesized base stocks, high quality re-refined base stocks, and contain a special blend of additives that keep engines clean of harmful carbon deposits, varnishes and resins. With recent additive improvements, these more robust offerings are equipped to negate the destructive effects of Low Speed Pre-Ignition and provide improved Turbocharger protection by reducing turbo coking and deposits.

Eco Ultra Full Synthetic Engine Oils also protect engines from sludge, rust and acid build-up. These oils perform efficiently in gasoline engines and are outstanding for stop-and-go taxi fleets, city delivery vehicles and public utility fleets.

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SAE 0W-20</u>	<u>SAE 5W-20</u>	<u>SAE 5W-30</u>	<u>SAE 10W-30</u>
Viscosity @ -35°C, cP	D-5293	6000	N/A	N/A	N/A
Viscosity @ -30°C, cP	D-5293	N/A	6000	5800	N/A
Viscosity @ -25°C, cP	D-5293	N/A	N/A	N/A	5000
Viscosity @ 40°C, cSt	D-445	45.00	44.00	58.00	63.00
Viscosity @ 100°C, cSt	D-445	8.50	8.30	10.50	10.80
Viscosity Index	D-2270	170	160	170	170
Flash Point, COC, °C	D-92	213	213	213	213
Flash Point, COC, °F	D-92	415	415	415	415
Pour Point, °C	D-97	-40	-40	-40	-40
Pour Point, °F	D-97	-40	-40	-40	-40
Color	D-1500	2.0	2.0	2.0	2.0
Gravity, °API	D-287	32.0	35.5	36.0	36.0

Meets or exceeds the following tests and requirements:

API Service Classification – SQ, SP, SN PLUS, SN, ILSAC GF-7A

Chrysler MS-11999, MS-12007, MS-12015, MS-6395-S

Resource Conserving

Ford Motor Company – WSS-M2C960-A1 (5W-20), WSS-M2C961-A1 (5W-30), WSS-M2C962-A1 (0W-20)

Honda/Toyota Genuine Oils

EO-21 ECO ULTRA FS EO/04.06.26

Exclusively offered by

moove

moovelube.com